pixis:^{be}

Bowflag [®] 100

Plug-in system for curved elegance

Indoor and outdoor application

Variable exchangeable ground fittings

For selected shapes positive images on both sides are possible









Digital Printing and Displays by www.pixis.be

Bowflag ® 100

Its sophisticated design, highest flexibility and easy handling make the Bowflag ^{*} one of the most commonly used marketing tools for events.

Various shapes and heights up to 5.2 m allow for eye-catching and expressive company and product presentations.



Please note:

To avoid damages please only use single sided Bowflag * 100 up to wind force scale 6 bft and Bowflag * 100 double sided up to wind force scale 4 bft.



Tip: Bowflag °T – table sail in stylish drop shape

With a total height of 55 cm, it is one of the "big" small advertising materials.

Advantages

- Full usage of advertising space, as sleeve for rod is part of the printed flag material
- Rod segments are hidden in a sleeve made of flag material
- · Sophisticated plug-in system of narrowing aluminium rods, coated to prevent staining
- No hassle with sliding down or breaking rod segments
- Bases with integrated swivel, allowing the flag to move 360° with the wind
- · Variable exchangeable ground fittings
- · Variety of sizes and shapes
- · Easy assembly within 3 minutes
- Usage of proven flag materials
 Multiflag [°], Varioflag [°]A and Varioflag [°]

Double sided banner

For selected shapes (please look at the right side) positive images on both sides are possible by using double sided banner.

Elements

Size	Elements
XL	3 aluminium segments, 2 fibreglass segments supplied in a bag
L	2 aluminium segments, 2 fibreglass segments supplied in a bag
м	2 aluminium segments, 2 fibreglass segments supplied in a bag
S	2 aluminium segments, 2 fibreglass segments supplied in a bag
xs	1 aluminium segment, 2 fibreglass segments supplied in a bag
XXS	1 aluminium segment, 1 fibreglass segment supplied in a bag











Digital Printing and Displays by www.pixis.be

	Bowflag * 100 with concave	bottom edge	XL	L	М	S	XS	XXS	
XL		system height (h) in cm	520	410	310	250	180	125	
		Ad space dimensions in cm	85x450	80x340	60x260	55x200	50x150	40x95	ی ج
	s xs	double sided banner possible			x	x	x	x	Ad spa
		distance ad space to the ground (a) in cm	70	70	50	50	25	25	, and the second s

	Bowflag * 100 with convexe	bottom edge	XL	L	М	S	XS	XXS	
, XL		system height (h) in cm	520	410	310	250	180	125	
		Ad space dimensions in cm	85x450	80x340	60x260	55x200	50x150	40x95	
	s xs	double sided banner possible			x	x	x	x	مd spa
	P P P P P	distance ad space to the ground (a) in cm	70	70	50	50	25	25	a a

	Bowflag * 100 with straight b	oottom edge	XL	L	М	S	XS	XXS		
, XL		system height (h) in cm	520	410	310	250	180	125		Î
		Ad space dimensions in cm	85x450	80x340	60x260	55x200	50x150	40x95	pace	
	s xs	double sided banner possible			x	x	x	x	Ad s	٩
		distance ad space to the ground (a) in cm	70	70	50	50	25	25	σ	

	Bowflag * 100 with angled l	pottom edge	XL	L	М	S	XS	XXS		
, XL		system height (h) in cm	520	410	310	250	180	125		1
		Ad space dimensions in cm	85x450	80x340	60x260	55x200	50x150	40x95	<u>c</u> e	
	s xs	double sided banner possible			x	x	x	x	Ad spa	۲
		distance ad space to the ground (a) in cm	70	70	50	50	25	25	a	

Bowflag * 100 drop		XL	L	M	S	XS	XXS	
XL	system height (h) in cm	430	335	255	220	160	110	
M	Ad space dimensions in cm	120x360	110x265	95x205	75x170	55x130	40x80	d space
S XS	double sided banner possible	x	x	x	x			۲ ح
	distance ad space to the ground (a) in cm	70	70	50	50	25	25	D D D D D D D D D D D D D D D D D D D

Scope of delivery

- $\cdot\,$ Pole segments supplied in a bag
- · Choose your base according to the place of usage
- · Solid carrying case available on request



 Scope of delivery (here with image, rod, ground spike with swivel)



Carrying case

Ground Fittings, Accessories and Wall-Mount

Ground fittings for Bowfl	ag * 100	XL L	Μ	S	XS	xxs		Ground fitting
Crossbar Base 70 x 70 cm, with swivel, chrome-plated steel, ca. 3,1 kg	X	• •	•		•	0 0		Screw-in-grou mount with Ø 16,6 mm, ca. 0,7 kg
Crossbar Base 55x55cm, with swivel, powder-coated steel, ca. 1,5 kg	>>	• •	•		•	•		Tube Base w applicable on extra weight, ca. 6,0 kg
Base Plate 55 x 55 cm with swivel, powder-coated steel, ca. 18,5 kg		•						Tube Base ecc with swivel, a only with extra ca. 3,5 kg
Base Plate 40 x 40 cm with swivel, powder-coated steel, ca. 9 kg		• •	•					Concrete Base without swive plastic-coated ca. 20 kg
Base Plate 40 x 40 cm without swivel, pow- der-coated steel, ca. 9 kg		• •	•					Water filling B plastic, water filling 3 sand filling 52
Base Plate 30 x 30 cm without swivel, pow- der-coated steel, ca. 3,9 kg		0 0			•	•		Water filling B with swivel, v without suspe water filling 9
Base Plate 18 x 30 cm without swivel, pow- der-coated steel, ca. 2,5 kg		• rec	comm	ende	• ed	pos	sible	Ground Spike with or withou length ca. 60 ca. 1,0 kg

Ground fittings for Bow	flag * 100	XL	L	М	S	XS	XXS	
Screw-in-ground mount with swivel, Ø 16,6 mm, ca. 0,7 kg	-	•	•	•	•			
Tube Base with swivel, applicable only with extra weight, ca. 6,0 kg	Ð	•	•	•				
Tube Base economy with swivel, applicable only with extra weight, ca. 3,5 kg	1	•	•	•				
Concrete Base with or without swivel, plastic-coated, ca. 20 kg	5	•	•	•		0		
Water filling Base P2, plastic, water filling 301 sand filling 52 kg	0	•						
Water filling Base P3, with swivel, with or without suspension, water filling 9 l		• ava	• ailal	• ole fi	• rom	• July :	• 2009	
Ground Spike with or without swivel, length ca. 60 cm, ca. 1,0 kg	1/4	•	• reco	• omm	• nend	ed	• pos	sible

Accessories		recommended for
Weight Bag for water filling capacity ca. 101		Crossbar Bases, Base Plates
Sand- and Snow Exten- sion length ca. 80 cm, yellow chromated steel	/	Ground Spikes

XL L M S XS XXS

possible

recommended

Wall-Mount for Bowflag * 100

Wall-Mount, 30° powder-coated steel,

ca. 0,5 kg

Accessories		recommended for
Stakes length ca.16 cm, powder-coated steel	17	Crossbar Bases, Base Plates
Ground spike-stabiliser Ø 15 cm, steel, zinc-plated	٩	Ground Spikes

We will be happy to advice you on the choice and use.